DragonEye speed LIDAR®

ADVANCED HAND-HELD SPEED ENFORCEMENT

Designed to be the new leader in law enforcement speed measurement, the DragonEye Speed Lidar[®] provides superior target acquisition and range performance in a compact, lightweight package. With 4-point rubber cushioning and robust, waterproof mechanical design, the DragonEye Speed Lidar [®] stays on target when other units are headed for the shop. Incorporating advanced features such as obstruction mode, anti-jamming, onboard data logging and cloud storage options, the DragonEye Speed Lidar[®] gives you the latest in speed enforcement technology.



Advanced Electro-Optical Systems

DragonEye Technology, LLC 5680 Oakbrook Parkway Suite 149 Norcross, GA 30093 Tel: 770-441-7712 x156 Fax: 770-441-7713

Email: info@dragoneyetech.com Web: www.dragoneyetech.com



DragonEye speed LIDAR® ADVANCED HAND-HELD SPEED ENFORCEMENT

Key Features

- Superior vehicle acquisition and tracking algorithms even at long ranges with detailed accuracy checking routines.
- True color head-up display shows accurate vehicle colors.
- User selectable DOT or OVAL aiming reticle.
- Rugged construction: Shock resistant, floating internal aluminum optical bench structure with four point external rubber cushion, maintains alignment in tough law enforcement conditions.
- New Bluetooth connectivity for live data streaming.
- New onboard data storage. Recall up to 6 months of speed/range records with date stamp.
- Compact, lightweight and extremely well balanced in your hand.
- High resolution rear matrix display with auto-on backlight.
- Easy to use controls with dedicated brightness, volume and weather buttons.
- Advanced anti-jamming allows speed readings while most guns are blanked or display error codes.
- Obstruction Mode allows targeting through tree limbs wires and fences.
- Previous Speeds Recall Function.
- Advanced power saving features yields extended battery life.

Specifications

Weight: 2.5 lb (1.14 kg) with batteries

Dimensions: 4.5 x 6.75 x 9.75 inches (11.4 x 17.1 x 24.8 cm)

Acquisition Time: 1/3 Second

Speed Accuracy: +/- 1 MPH

+/- 1 km/h available

Max. Range: 6000 ft (1828 m)

Minimum Range: Speed Mode 50 ft (15 m)

Range Mode 10 ft (3 m) Weather Mode 250 ft (76 m) (Custom Ranges Available)

Speed Max/Min: 5 to 200 MPH (8 to 320 km/h)

(zero speed option available)

Speed Mode: True, full time, continuous tracking history

Dist. Accuracy +/- 0.5 ft (+/- 15.0 cm) one sigma

Dist. Resolution: 0.1 ft (3.0 cm)

Beam Width: 2.5 feet @ 1000 ft (2 5mr)

Laser Source: Diode, 905 +/- 10 nm

Eye Safety: FDA CDRH Class 1

Temperature: -22° F to $+140^{\circ}$ F (-30° C to $+60^{\circ}$ C)

Waterproof: IP67

Power Source: Two C-cells; High Quality Alkaline or NiMH

Rechargeable

Battery Life: 24 – 32 Hours of Operation (Alkaline C-

cell), typical use

Data Interface: RS 232, Bluetooth

Certification: IACP, CE

PLEASE NOTE THESE SPECIFICATIONS REPRESENT STANDARD MODEL PERFORMANCE. MODIFIED SPECIFICATIONS MAY EXIST FOR CUSTOM REQUIREMENTS OR TO COMPLY WITH UNIQUE STATE OR COUNTRY REGULATIONS.